

Iveco Daily

35S14H 3750 Nacelle Smart P170 TXE E 2.3 Diesel 136ch

Diesel - Manual - 905km - 12/2022

Ref 58247



[All images](#)

Iveco Daily

35S14H 3750 Nacelle Smart P170 TXE E 2.3 Diesel 136ch

Diesel - Manual - 905km - 12/2022

Ref 58247

Description

Make	Iveco
Model	Daily
Description	35S14H 3750 Nacelle Smart P170 TXE E 2.3 Diesel 136ch
Mileage	905 km
Type	LCV / Commercial
Body type	Chassis double cabine
Doors	2
Seats	2
Exterior color	White
Interior color	Black
Upholstery	Cloth

Technical

Fuel type	Diesel	Gears	6
Gearbox	Manual	Cylinders	0
Cylinder capacity	2287 cc	Horse power	136 hp
Power KW	100 kw		
Drive train	Front		

Dimensions

Weight empty	3325 kg	Weight max	7000 kg
Wheelbase	375 cm	Length	690 cm
Height	291 cm	Width	219 cm

Iveco Daily

35S14H 3750 Nacelle Smart P170 TXE E 2.3 Diesel 136ch

Diesel - Manual - 905km - 12/2022

Ref 58247

Registration and Warranty

First Registration 29-12-2022

Warranty start 29-12-2022

Options

Comfort

Electric windows front

Safety

Speed limit control system

Lights daytime running

Electronic parking brake

Iveco Daily

35S14H 3750 Nacelle Smart P170 TXE E 2.3 Diesel 136ch

Diesel - Manual - 905km - 12/2022

Ref 58247

Equipment

Platform height: 14.90 m	Electric handbrake
Passenger seat with three-way adjustment	70L streamlined fuel tank
16" steel wheels	Front suspension: double wishbone with steel transverse leaf spring
Two-seat passenger bench	Speed limiter
Manually adjustable driver's seat	Two-seat passenger bench with 3-point seatbelt and folding backrest
Expansion module + CAN Open interface	PTO solenoid 2835.6
Daytime running lights	Turret rotation: 370
Basket capacity: 250 kg	Open central storage
Platform rotation: 2x90	Fixed rear underrun protection bar
Working height: 16.90 m	Gear ratio: 3.91
Palfinger Smart P170 TXE E Aerial Work Platform	2 kg fire extinguisher mount
Power windows (one-touch on driver's side)	Black radiator grille
Basket load capacity: 230 kg	Max. outreach: 11.80 m
Rear axle with single-reduction motor drive and single wheel	Rear mechanical suspension with low-flex parabolic springs and reinforced parabolic leaf spring

Image gallery





















